

preserving action. Generally, a radio receiver is often defined in terms of front-end and back-end characteristics. The front-end of the receiver encompasses all of the Radio Frequency (RF) circuitry whereas the back-end encompasses all of the base-band processing circuitry. As used in this application, the term “circuitry” refers to both: (1) hardware-only implementations (such as implementations in only analog and/or digital circuitry), and (2) to combinations of circuitry and software (and/or firmware) (such as, if applicable to the particular context, to a combination of processor(s), including digital signal processor(s), software, and memory(ies) that work together to cause an apparatus, such as a mobile phone or server, to perform various functions). This definition of “circuitry” applies to all uses of this term in this application, including in any claims. As a further example, as used in this application and if applicable to the particular context, the term “circuitry” would also cover an implementation of merely a processor (or multiple processors) and its (or their) accompanying software/or firmware. The term “circuitry” would also cover if applicable to the particular context, for example, a baseband integrated circuit or applications processor integrated circuit in a mobile phone or a similar integrated circuit in a cellular network device or other network devices.

[0102] Pertinent internal components of the telephone include a Main Control Unit (MCU) **1203**, a Digital Signal Processor (DSP) **1205**, and a receiver/transmitter unit including a microphone gain control unit and a speaker gain control unit. A main display unit **1207** provides a display to the user in support of various applications and mobile terminal functions that perform or support the steps of processing one or more user inputs to identify at least one potential privacy conflict, thereby causing a collaboration of one or more privacy policies for at least one privacy preserving action. The display **1207** includes display circuitry configured to display at least a portion of a user interface of the mobile terminal (e.g., mobile telephone). Additionally, the display **1207** and display circuitry are configured to facilitate user control of at least some functions of the mobile terminal. An audio function circuitry **1209** includes a microphone **1211** and microphone amplifier that amplifies the speech signal output from the microphone **1211**. The amplified speech signal output from the microphone **1211** is fed to a coder/decoder (CO-DEC) **1213**.

[0103] A radio section **1215** amplifies power and converts frequency in order to communicate with a base station, which is included in a mobile communication system, via antenna **1217**. The power amplifier (PA) **1219** and the transmitter/modulation circuitry are operationally responsive to the MCU **1203**, with an output from the PA **1219** coupled to the duplexer **1221** or circulator or antenna switch, as known in the art. The PA **1219** also couples to a battery interface and power control unit **1220**.

[0104] In use, a user of mobile terminal **1201** speaks into the microphone **1211** and his or her voice along with any detected background noise is converted into an analog voltage. The analog voltage is then converted into a digital signal through the Analog to Digital Converter (ADC) **1223**. The control unit **1203** routes the digital signal into the DSP **1205** for processing therein, such as speech encoding, channel encoding, encrypting, and interleaving. In one embodiment, the processed voice signals are encoded, by units not separately shown, using a cellular transmission protocol such as enhanced data rates for global evolution (EDGE), general

packet radio service (GPRS), global system for mobile communications (GSM), Internet protocol multimedia subsystem (IMS), universal mobile telecommunications system (UMTS), etc., as well as any other suitable wireless medium, e.g., microwave access (WiMAX), Long Term Evolution (LTE) networks, code division multiple access (CDMA), wideband code division multiple access (WCDMA), wireless fidelity (WiFi), satellite, and the like, or any combination thereof.

[0105] The encoded signals are then routed to an equalizer **1225** for compensation of any frequency-dependent impairments that occur during transmission through the air such as phase and amplitude distortion. After equalizing the bit stream, the modulator **1227** combines the signal with a RF signal generated in the RF interface **1229**. The modulator **1227** generates a sine wave by way of frequency or phase modulation. In order to prepare the signal for transmission, an up-converter **1231** combines the sine wave output from the modulator **1227** with another sine wave generated by a synthesizer **1233** to achieve the desired frequency of transmission. The signal is then sent through a PA **1219** to increase the signal to an appropriate power level. In practical systems, the PA **1219** acts as a variable gain amplifier whose gain is controlled by the DSP **1205** from information received from a network base station. The signal is then filtered within the duplexer **1221** and optionally sent to an antenna coupler **1235** to match impedances to provide maximum power transfer. Finally, the signal is transmitted via antenna **1217** to a local base station. An automatic gain control (AGC) can be supplied to control the gain of the final stages of the receiver. The signals may be forwarded from there to a remote telephone which may be another cellular telephone, any other mobile phone or a land-line connected to a Public Switched Telephone Network (PSTN), or other telephony networks.

[0106] Voice signals transmitted to the mobile terminal **1201** are received via antenna **1217** and immediately amplified by a low noise amplifier (LNA) **1237**. A down-converter **1239** lowers the carrier frequency while the demodulator **1241** strips away the RF leaving only a digital bit stream. The signal then goes through the equalizer **1225** and is processed by the DSP **1205**. A Digital to Analog Converter (DAC) **1243** converts the signal and the resulting output is transmitted to the user through the speaker **1245**, all under control of a Main Control Unit (MCU) **1203** which can be implemented as a Central Processing Unit (CPU).

[0107] The MCU **1203** receives various signals including input signals from the keyboard **1247**. The keyboard **1247** and/or the MCU **1203** in combination with other user input components (e.g., the microphone **1211**) comprise a user interface circuitry for managing user input. The MCU **1203** runs a user interface software to facilitate user control of at least some functions of the mobile terminal **1201** to process one or more user inputs to identify at least one potential privacy conflict, thereby causing a collaboration of one or more privacy policies for at least one privacy preserving action. The MCU **1203** also delivers a display command and a switch command to the display **1207** and to the speech output switching controller, respectively. Further, the MCU **1203** exchanges information with the DSP **1205** and can access an optionally incorporated SIM card **1249** and a memory **1251**. In addition, the MCU **1203** executes various control functions required of the terminal. The DSP **1205** may, depending upon the implementation, perform any of a variety of conventional digital processing functions on the